



T_{aper}
B_{ore}


V-pulleys




TYPE1




TYPE2




TYPE3




TYPE4




TYPE5




TYPE6



TYPE7



TYPE8



TYPE9

PART NO.	NO. OF GROOVES	P.D	O.D	TYPE	BUSH NO.	MAX BORE	E	F	J	K	L	M	N
SPB 100-01	1	100.0	107.0	1	1610	42	—	25	—	—	25	—	—
SPB 112-01	1	112.0	119.0	1	1610	42	—	25	—	—	25	—	—
SPB 118-01	1	118.0	125.0	1	1610	42	—	25	—	—	25	—	—
SPB 125-01	1	125.0	132.0	1	1610	42	—	25	—	—	25	—	—
SPB 132-01	1	132.0	139.0	1	1610	42	—	25	—	—	25	—	—
SPB 140-01	1	140.0	147.0	1	1610	42	—	25	—	—	25	—	—
SPB 150-01	1	150.0	157.0	1	1610	42	—	25	—	—	25	—	—
SPB 160-01	1	160.0	167.0	1	1610	42	—	25	—	—	25	—	—
SPB 170-01	1	170.0	177.0	1	1610	42	—	25	—	—	25	—	—
SPB 180-01	1	180.0	187.0	6	1610	42	10	25	137	—	25	—	80
SPB 190-01	1	190.0	197.0	7	2012	50	10	25	147	3.5	32	3.5	100
SPB 200-01	1	200.0	207.0	7	2012	50	10	25	157	3.5	32	3.5	100
SPB 212-01	1	212.0	219.0	7	2012	50	10	25	169	3.5	32	3.5	100
SPB 224-01	1	224.0	231.0	7	2012	50	0	25	181	3.5	32	3.5	100
SPB 236-01	1	236.0	243.0	7	2012	50	10	25	193	3.5	32	3.5	100
SPB 250-01	1	250.0	257.0	7	2012	50	10	25	207	3.5	32	3.5	100
SPB 280-01	1	280.0	287.0	7	2012	50	10	25	237	3.5	32	3.5	100
SPB 315-01	1	315.0	322.0	7	2012	50	10	25	272	3.5	32	3.5	100


Standard bore dimensions of BTL bushings

Bushing	Stock Bores																			
	11	12	14	16	18	19	20	22	24	25	28	30	32	35	38	40	42	45	48	50
1210	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
1610				*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
2012					*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
2517						*	*	*	*	*	*	*	*	*	*	*	*	*	*	*


* shallow keyway

T_{aper}
B_{ore}


V-pulleys




TYPE1




TYPE2




TYPE3




TYPE4




TYPE5




TYPE6



TYPE7




TYPE8




TYPE9

PART NO.	NO. OF GROOVES	P.D	O.D	TYPE	BUSH NO.	MAX BORE	E	F	J	K	L	M	N
SPB 100-02	2	100.0	107.0	8	1610	42	—	44	62	—	25	19	—
SPB 112-02	2	112.0	119.0	2	1610	42	—	44	72	—	25	19	—
SPB 118-02	2	118.0	127.0	2	1610	42	—	44	78	—	25	19	—
SPB 125-02	2	125.0	132.0	2	2012	50	—	44	82	—	32	12	—
SPB 132-02	2	132.0	139.0	2	2012	50	—	44	89	—	32	12	—
SPB 140-02	2	140.0	147.0	2	2012	50	—	44	97	—	32	12	—
SPB 150-02	2	150.0	157.0	2	2012	50	—	44	107	—	32	12	—
SPB 160-02	2	160.0	167.0	2	2012	50	—	44	117	—	32	12	—
SPB 170-02	2	170.0	177.0	2	2012	50	—	44	127	—	32	12	—
SPB 180-02	2	180.0	187.0	1	2517	60	—	44	—	—	45	1	120
SPB 190-02	2	190.0	197.0	1	2517	60	—	44	—	—	45	1	120
SPB 200-02	2	200.0	207.0	1	2517	60	—	44	—	—	45	1	120
SPB 212-02	2	212.0	219.0	7	2517	60	10	44	169	—	45	1	120
SPB 224-02	2	224.0	231.0	7	2517	60	10	44	181	1	45	—	120
SPB 236-02	2	236.0	243.0	7	2517	60	10	44	193	1	45	—	120
SPB 250-02	2	250.0	257.0	7	2517	60	10	44	207	1	45	—	120
SPB 280-02	2	280.0	287.0	7	2517	60	12	44	237	1	45	—	120
SPB 300-02	2	300.0	307.0	7	2517	60	12	44	257	1	45	—	120
SPB 315-02	2	315.0	322.0	7	2517	60	12	44	272	1	45	—	120
SPB 335-02	2	335.0	342.0	7	2517	60	12	44	292	1	45	—	120
SPB 355-02	2	355.0	362.0	4	3020	75		44	312	3.5	51	3.5	150
SPB 400-02	2	400.0	407.0	4	3020	75		44	357	3.5	51	3.5	150
SPB 450-02	2	450.0	457.0	4	3020	75		44	407	3.5	51	3.5	150
SPB 500-02	2	500.0	507.0	4	3020	75		44	457	3.5	51	3.5	150
SPB 560-02	2	560.0	567.0	4	3030	75		44	517	4	76	28	150
SPB 630-02	2	630.0	637.0	4	3030	75		44	587	4	76	28	150


Taper Bore V-pulleys




TYPE1




TYPE2




TYPE3




TYPE4




TYPE5




TYPE6



TYPE7




TYPE8




TYPE9

PART NO.	NO. OF GROOVES	P.D	O.D	TYPE	BUSH NO.	MAX BORE	E	F	J	K	L	M	N
SPB 100-03	3	100.0	107.0	8	1610	42	—	63	57	—	25	38	—
SPB 112-03	3	112.0	119.0	2	1610	42	—	63	72	—	25	38	—
SPB 118-03	3	118.0	125.0	2	1610	42	—	63	78	—	25	38	—
SPB 125-03	3	125.0	132.0	2	2012	50	—	63	82	—	32	31	—
SPB 132-03	3	132.0	139.0	2	2012	50	—	63	89	—	32	31	—
SPB 140-03	3	140.0	147.0	2	2012	50	—	63	97	—	32	31	—
SPB 150-03	3	150.0	157.0	2	2517	60	—	63	107	—	45	18	—
SPB 160-03	3	160.0	167.0	2	2517	60	—	63	117	—	45	18	—
SPB 170-03	3	170.0	177.0	2	2517	60	—	63	127	—	45	18	—
SPB 180-03	3	180.0	187.0	2	2517	60	—	63	137	—	45	18	—
SPB 190-03	3	190.0	197.0	2	2517	60	—	63	147	—	45	18	—
SPB 200-03	3	200.0	207.0	2	2517	60	—	63	157	—	45	18	—
SPB 212-03	3	212.0	219.0	6	2517	60	12	63	169	—	45	18	120
SPB 224-03	3	224.0	231.0	6	2517	60	12	63	181	—	45	18	120
SPB 236-03	3	236.0	243.0	6	2517	60	10	63	193	—	45	18	120
SPB 250-03	3	250.0	257.0	6	3020	75	12	63	207	—	51	12	150
SPB 280-03	3	280.0	287.0	6	3020	75	13	63	237	6	51	6	150
SPB 300-03	3	300.0	307.0	6	3020	75	13	63	257	6	51	6	150
SPB 315-03	3	315.0	322.0	6	3020	75	13	63	272	6	51	6	150
SPB 335-03	3	335.0	342.0	6	3020	75	13	63	292	6	51	6	150
SPB 355-03	3	355.0	362.0	5	3020	75	—	63	312	6	51	6	150
SPB 400-03	3	400.0	407.0	4	3535	90	—	63	357	13	89	13	170
SPB 450-03	3	450.0	457.0	4	3535	90	—	63	407	—	89	26	170
SPB 500-03	3	500.0	507.0	4	3535	90	—	63	457	—	89	26	170
SPB 560-03	3	560.0	567.0	4	3535	90	—	63	517	—	89	26	170
SPB 630-03	3	630.0	637.0	4	3535	90	—	63	587	—	89	26	170
SPB 710-03	3	710.0	717.0	4	3535	90	—	63	664	4	89	22	170
SPB 800-03	3	800.0	807.0	4	3535	90	—	63	754	4	89	22	170
SPB 900-03	3	900.0	907.0	4	3535	90	—	63	854	4	89	22	170
SPB 1000-03	3	1000.0	1007.0	4	4040	100	—	63	954	6	102	33	200
SPB 1250-03	3	1250.0	1257.0	4	4040	100	—	63	1204	6	102	33	200


Taper Bore V-pulleys




TYPE1




TYPE2




TYPE3




TYPE4




TYPE5




TYPE6



TYPE7




TYPE8




TYPE9

PART NO.	NO. OF GROOVES	P.D	O.D	TYPE	BUSH NO.	MAX BORE	E	F	J	K	L	M	N
SPB 125-04	4	125.0	132.0	3	2012	50	—	82	82	25	32	25	—
SPB 132-04	4	132.0	139.0	3	2012	50	—	82	89	25	32	25	—
SPB 140-04	4	140.0	147.0	3	2517	60	—	82	97	18.5	45	18.5	—
SPB 150-04	4	150.0	157.0	3	2517	60	—	82	107	18.5	45	18.5	—
SPB 160-04	4	160.0	167.0	3	2517	60	—	82	117	18.5	45	18.5	—
SPB 170-04	4	170.0	177.0	3	2517	60	—	82	127	18.5	45	18.5	—
SPB 180-04	4	180.0	187.0	3	2517	60	—	82	137	18.5	45	18.5	—
SPB 190-04	4	190.0	197.0	3	2517	60	—	82	147	18.5	45	18.5	—
SPB 200-04	4	200.0	207.0	3	3020	75	—	82	157	15.5	51	15.5	—
SPB 212-04	4	212.0	219.0	3	3020	75	—	82	169	15.5	51	15.5	—
SPB 224-04	4	224.0	231.0	3	3020	75	—	82	181	15.5	51	15.5	—
SPB 236-04	4	236.0	243.0	3	3020	75	—	82	193	15.5	51	15.5	—
SPB 250-04	4	250.0	257.0	6	3020	75	14	82	207	15.5	51	15.5	150
SPB 280-04	4	280.0	287.0	6	3020	75	16	82	237	15.5	51	15.5	150
SPB 300-04	4	300.0	307.0	6	3020	75	16	82	257	15.5	51	15.5	150
SPB 315-04	4	315.0	322.0	7	3535	90	16	82	272	3.5	89	3.5	170
SPB 335-04	4	335.0	342.0	7	3535	90	16	82	292	3.5	89	3.5	170
SPB 355-04	4	355.0	362.0	7	3535	90	16	82	312	3.5	89	3.5	170
SPB 400-04	4	400.0	407.0	4	3535	90	—	82	357	3.5	89	3.5	170
SPB 450-04	4	450.0	457.0	4	3535	90	—	82	407	—	89	7	170
SPB 500-04	4	500.0	507.0	4	3535	90	—	82	457	—	89	7	170
SPB 560-04	4	560.0	567.0	4	3535	90	—	82	517	—	89	7	170
SPB 630-04	4	630.0	637.0	4	3535	90	—	82	587	—	89	7	170
SPB 710-04	4	710.0	717.0	4	3535	90	—	82	664	3.5	89	3.5	187
SPB 800-04	4	800.0	807.0	4	4040	100	—	82	754	4	102	16	200
SPB 900-04	4	900.0	907.0	4	4040	100	—	82	854	4	102	16	216
SPB 1000-04	4	1000.0	1007.0	4	4040	100	—	82	954	4	102	16	216
SPB 1250-04	4	1250.0	1257.0	4	4545	110	—	82	1204	6	114	26	225


Taper Bore V-pulleys




TYPE1




TYPE2




TYPE3




TYPE4




TYPE5




TYPE6



TYPE7




TYPE8




TYPE9

PART NO.	NO. OF GROOVES	P.D	O.D	TYPE	BUSH NO.	MAX BORE	E	F	J	K	L	M	N
SPB 125-05	5	125.0	132.0	8	2012	50	—	101	82	69	32	—	—
SPB 132-05	5	132.0	139.0	8	2517	60	—	101	89	56	45	—	—
SPB 140-05	5	140.0	147.0	3	2517	60	—	101	97	28	45	28	—
SPB 150-05	5	150.0	157.0	3	2517	60	—	101	107	28	45	28	—
SPB 160-05	5	160.0	167.0	3	2517	60	—	101	117	28	45	28	—
SPB 170-05	5	170.0	177.0	3	3020	75	—	101	127	25	51	25	—
SPB 180-05	5	180.0	187.0	3	3020	75	—	101	137	25	51	25	—
SPB 190-05	5	190.0	197.0	3	3020	75	—	101	147	25	51	25	—
SPB 200-05	5	200.0	207.0	3	3020	75	—	101	157	25	51	25	—
SPB 212-05	5	212.0	219.0	3	3020	75	—	101	169	25	51	25	—
SPB 224-05	5	224.0	231.0	3	3020	75	—	101	181	25	51	25	—
SPB 236-05	5	236.0	243.0	3	3535	90	—	101	193	6	89	6	—
SPB 250-05	5	250.0	257.0	3	3535	90	—	101	207	6	89	6	—
SPB 280-05	5	280.0	287.0	6	3535	90	18	101	237	6	89	6	170
SPB 300-05	5	300.0	307.0	6	3535	90	18	101	257	6	89	6	170
SPB 315-05	5	315.0	322.0	6	3535	90	18	101	272	6	89	6	170
SPB 335-05	5	335.0	342.0	6	3535	90	16	101	292	6	89	6	170
SPB 355-05	5	355.0	362.0	5	3535	90	—	101	312	6	89	6	170
SPB 400-05	5	400.0	407.0	5	3535	90	—	101	357	6	89	6	170
SPB 450-05	5	450.0	457.0	5	3535	90	—	101	407	—	89	12	170
SPB 500-05	5	500.0	507.0	5	3535	90	—	101	457	—	89	12	170
SPB 560-05	5	560.0	567.0	4	4040	100	—	101	517	—	102	1	200
SPB 630-05	5	630.0	637.0	4	4040	100	—	101	587	—	102	1	200
SPB 710-05	5	710.0	717.0	4	4040	100	—	101	664	0.5	102	0.5	200
SPB 800-05	5	800.0	807.0	4	4040	100	—	101	754	0.5	102	0.5	200
SPB 900-05	5	900.0	907.0	4	4545	110	—	101	854	6.5	114	6.5	225
SPB 1000-05	5	1000.0	1007.0	4	4545	110	—	101	954	6.5	114	6.5	225
SPB 1250-05	5	1250.0	1257.0	4	4545	110	—	101	1204	6.5	114	6.5	225


Taper Bore V-pulleys




TYPE1




TYPE2




TYPE3




TYPE4




TYPE5




TYPE6



TYPE7



TYPE8




TYPE9


PART NO.	NO. OF GROOVES	P.D	O.D	TYPE	BUSH NO.	MAX BORE	E	F	J	K	L	M	N
SPB 140-06	6	140.0	147.0	3	2517	60	—	120	97	37.5	45	37.5	—
SPB 150-06	6	150.0	157.0	3	2517	60	—	120	107	37.5	45	37.5	—
SPB 160-06	6	160.0	167.0	3	3020	75	—	120	117	34.5	51	34.5	—
SPB 170-06	6	170.0	177.0	3	3020	75	—	120	127	34.5	51	34.5	—
SPB 180-06	6	180.0	187.0	3	3020	75	—	120	137	34.5	51	34.5	—
SPB 190-06	6	190.0	197.0	3	3020	75	—	120	147	34.5	51	34.5	—
SPB 200-06	6	200.0	207.0	3	3020	75	—	120	157	34.5	51	34.5	—
SPB 212-06	6	212.0	219.0	3	3535	90	—	120	169	15.5	89	15.5	—
SPB 224-06	6	224.0	231.0	3	3535	90	—	120	181	15.5	89	15.5	—
SPB 236-06	6	236.0	243.0	3	3535	90	—	120	193	15.5	89	15.5	—
SPB 250-06	6	250.0	257.0	3	3535	90	—	120	207	15.5	89	15.5	—
SPB 280-06	6	280.0	287.0	6	3535	90	18	120	237	15.5	89	15.5	170
SPB 300-06	6	300.0	307.0	6	3535	90	18	120	257	15.5	89	15.5	170
SPB 315-06	6	315.0	322.0	6	3535	90	18	120	272	15.5	89	15.5	170
SPB 335-06	6	335.0	342.0	6	3535	90	18	120	292	15.5	89	15.5	170
SPB 355-06	6	355.0	362.0	6	3535	90	18	120	312	15.5	89	15.5	170
SPB 400-06	6	400.0	407.0	5	3535	90	—	120	357	15.5	89	15.5	170
SPB 450-06	6	450.0	457.0	5	4040	100	—	120	407	—	102	18	200
SPB 500-06	6	500.0	507.0	5	4040	100	—	120	457	—	102	18	200
SPB 560-06	6	560.0	567.0	5	4040	100	—	120	517	—	102	18	200
SPB 630-06	6	630.0	637.0	5	4040	100	—	120	587	—	102	18	200
SPB 710-06	6	710.0	717.0	5	4040	100	—	120	664	9	102	9	216
SPB 800-06	6	800.0	807.0	5	4545	110	—	120	754	3	114	3	225
SPB 900-06	6	900.0	907.0	5	4545	110	—	120	854	3	114	3	225
SPB 1000-06	6	1000.0	1007.0	5	4545	110	—	120	954	3	114	3	225
SPB 1250-06	6	1250.0	1257.0	4	5050	125	—	120	1204	3.5	127	3.5	245

**T_{aper}
B_{ore}**


V-pulleys




TYPE1




TYPE2




TYPE3




TYPE4




TYPE5




TYPE6



TYPE7




TYPE8




TYPE9

PART NO.	NO. OF GROOVES	P.D	O.D	TYPE	BUSH NO.	MAX BORE	E	F	J	K	L	M	N
SPB 160-08	8	160.0	167.0	3	3020	75	—	158	117	53.5	51	53.5	—
SPB 170-08	8	170.0	177.0	3	3030	75	—	158	127	41	76	41	—
SPB 180-08	8	180.0	187.0	3	3030	75	—	158	137	41	76	41	—
SPB 190-08	8	190.0	197.0	3	3030	75	—	158	147	41	76	41	—
SPB 200-08	8	200.0	207.0	3	3535	90	—	158	157	34.5	89	34.5	—
SPB 212-08	8	212.0	219.0	3	3535	90	—	158	169	34.5	89	34.5	—
SPB 224-08	8	224.0	231.0	3	3535	90	—	158	181	34.5	89	34.5	—
SPB 236-08	8	236.0	243.0	3	3535	90	—	158	193	34.5	89	34.5	—
SPB 250-08	8	250.0	257.0	3	3535	90	—	158	207	34.5	89	34.5	—
SPB 280-08	8	280.0	287.0	3	3535	90	—	158	237	34.5	89	34.5	—
SPB 300-08	8	300.0	307.0	6	3535	90	20	158	257	34.5	89	34.5	170
SPB 315-08	8	315.0	322.0	6	3535	90	18	158	272	34.5	89	34.5	170
SPB 335-08	8	335.0	342.0	6	3535	90	18	158	292	34.5	89	34.5	170
SPB 355-08	8	355.0	362.0	6	3535	90	18	158	312	34.5	89	34.5	170
SPB 400-08	8	400.0	407.0	5	4040	100	—	158	357	28	102	28	200
SPB 450-08	8	450.0	457.0	5	4040	100	—	158	407	28	102	28	200
SPB 500-08	8	500.0	507.0	5	4040	100	—	158	457	28	102	28	200
SPB 560-08	8	560.0	567.0	5	4545	110	—	158	517	22	114	22	225
SPB 630-08	8	630.0	637.0	5	4545	110	—	158	587	22	114	22	225
SPB 710-08	8	710.0	717.0	5	4545	110	—	158	664	22	114	22	225
SPB 800-08	8	800.0	807.0	5	4545	110	—	158	754	22	114	22	225
SPB 900-08	8	900.0	907.0	5	4545	110	—	158	854	22	114	22	225
SPB 1000-08	8	1000.0	1007.0	5	5050	125	—	158	954	15.5	127	15.5	245
SPB 1250-08	8	1250.0	1257.0	5	5050	125	—	158	1204	15.5	127	15.5	245


Taper Bore V-pulleys




TYPE1




TYPE2




TYPE3




TYPE4




TYPE5




TYPE6



TYPE7



TYPE8



TYPE9

PART NO.	NO. OF GROOVES	P.D	O.D	TYPE	BUSH NO.	MAX BORE	E	F	J	K	L	M	N
SPB 224-10	10	224.0	231.0	3	3535	90	—	196	181	53.5	89	53.5	—
SPB 236-10	10	236.0	243.0	3	3535	90	—	196	193	53.5	89	53.5	—
SPB 250-10	10	250.0	257.0	3	3535	90	—	196	207	53.5	89	53.5	—
SPB 280-10	10	280.0	287.0	3	3535	90	—	196	237	53.5	89	53.5	—
SPB 315-10	10	315.0	322.0	6	3535	90	18	196	272	53.5	89	53.5	170
SPB 335-10	10	335.0	342.0	6	4040	100	20	196	292	47	102	47	200
SPB 355-10	10	355.0	362.0	6	4040	100	20	196	312	47	102	47	200
SPB 400-10	10	400.0	407.0	5	4040	100	—	196	357	47	102	47	200
SPB 450-10	10	450.0	457.0	5	4545	110	—	196	407	41	114	41	225
SPB 500-10	10	500.0	507.0	5	4545	110	—	196	457	41	114	41	225
SPB 560-10	10	560.0	567.0	5	4545	110	—	196	517	41	114	41	225
SPB 630-10	10	630.0	637.0	5	4545	110	—	196	587	41	114	41	225
SPB 710-10	10	710.0	717.0	5	4545	110	—	196	664	41	114	41	225
SPB 800-10	10	800.0	807.0	5	4545	110	—	196	754	41	114	41	225
SPB 900-10	10	900.0	907.0	5	5050	125	—	196	854	34.5	127	34.5	245
SPB 1000-10	10	1000.0	1007.0	5	5050	125	—	196	954	34.5	127	34.5	245

Standard bore dimensions of BTL bushings

Bushing	Stock Bores																			
	25	28	30	32	35	38	40	42	45	48	50	55	60	65	70	75	80	85	90	95
3030	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
3535					*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
4040						*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
							*	*	*	*	*	*	*	*	*	*	*	*	*	*
5050								*	*	*	*	*	*	*	*	*	*	*	*	*