




Taper Bore V-pulleys




TYPE1




TYPE2




TYPE3




TYPE4




TYPE5




TYPE6



TYPE7




TYPE8




TYPE9

PART NO.	NO. OF GROOVES	P.D	O.D	TYPE	BUSH NO.	MAX BORE	E	F	J	K	L	M	N
SPC 200-03	3	200.0	209.6	3	2517	60	—	85	150	20	45	20	—
SPC 212-03	3	212.0	221.6	3	3020	75	—	85	162	17	51	17	—
SPC 224-03	3	224.0	233.6	3	3020	75	—	85	173	17	51	17	—
SPC 236-03	3	236.0	245.6	3	3020	75	—	85	185	17	51	17	—
SPC 250-03	3	250.0	259.6	3	3020	75	—	85	200	17	51	17	—
SPC 265-03	3	265.0	274.6	1	3535	90	—	85	209	—	89	4	170
SPC 280-03	3	280.0	289.6	1	3535	90	—	85	224	—	89	4	170
SPC 300-03	3	300.0	309.6	7	3535	90	18	85	249	2	89	2	170
SPC 315-03	3	315.0	324.6	7	3535	90	18	85	264	2	89	2	170
SPC 335-03	3	335.0	345.0	7	3535	90	18	85	284	2	89	2	170
SPC 355-03	3	355.0	365.0	7	3535	90	18	85	304	2	89	2	170
SPC 375-03	3	375.0	384.6	7	3535	90	20	85	324	2	89	2	170
SPC 400-03	3	400.0	409.6	4	3535	90	—	85	344	2	89	2	170
SPC 425-03	3	425.0	434.6	4	3535	90	—	85	369	2	89	2	170
SPC 450-03	3	450.0	459.6	4	3535	90	—	85	394	2	89	2	170
SPC 475-03	3	475.0	484.6	4	3535	90	—	85	419	2	89	2	170
SPC 500-03	3	500.0	509.6	4	3535	90	—	85	444	2	89	2	170
SPC 530-03	3	530.0	539.6	4	3535	90	—	85	474	2	89	2	170
SPC 560-03	3	560.0	569.6	4	3535	90	—	85	504	2	89	2	170
SPC 630-03	3	630.0	639.6	4	4040	100	—	85	574	8.5	102	8.5	200
SPC 800-03	3	800.0	809.6	4	4545	110	—	85	737	4	114	25	225
SPC 1000-03	3	1000.0	1009.6	4	5050	125	—	85	937	8	127	34	245
SPC 1250-03	3	1250.0	1259.6	4	5050	125	—	85	1187	8	127	34	245


Taper Bore V-pulleys




TYPE1




TYPE2




TYPE3




TYPE4




TYPE5




TYPE6



TYPE7




TYPE8




TYPE9

PART NO.	NO. OF GROOVES	P.D	O.D	TYPE	BUSH NO.	MAX BORE	E	F	J	K	L	M	N
SPC 200-04	4	200.0	209.6	3	3020	75	—	111	144	30	51	30	—
SPC 212-04	4	212.0	221.6	3	3020	75	—	111	156	30	51	30	—
SPC 224-04	4	224.0	233.6	3	3535	90	—	111	168	11	89	11	—
SPC 236-04	4	236.0	245.6	3	3535	90	—	111	180	11	89	11	—
SPC 250-04	4	250.0	259.6	3	3535	90	—	111	194	11	89	11	—
SPC 265-04	4	265.0	274.6	3	3535	90	—	111	209	11	89	11	—
SPC 280-04	4	280.0	289.6	3	3535	90	—	111	224	11	89	11	—
SPC 300-04	4	300.0	309.6	6	3535	90	20	111	244	11	89	11	170
SPC 315-04	4	315.0	324.6	6	3535	90	20	111	259	11	89	11	170
SPC 335-04	4	335.0	344.6	6	3535	90	20	111	279	11	89	11	170
SPC 355-04	4	355.0	365.0	6	3535	90	20	111	299	11	89	11	170
SPC 375-04	4	375.0	384.6	6	3535	90	25	111	319	11	89	11	170
SPC 400-04	4	400.0	409.6	5	3535	90	—	111	344	11	89	11	170
SPC 425-04	4	425.0	434.6	5	3535	90	—	111	369	11	89	11	170
SPC 450-04	4	450.0	459.6	5	3535	90	—	111	394	11	89	11	170
SPC 475-04	4	475.0	484.6	5	3535	90	—	111	419	11	89	11	170
SPC 500-04	4	500.0	509.6	5	3535	90	—	111	444	11	89	11	170
SPC 530-04	4	530.0	539.6	5	3535	90	—	111	474	11	89	11	170
SPC 560-04	4	560.0	569.6	5	4040	100	—	111	504	4.5	102	4.5	200
SPC 630-04	4	630.0	639.6	4	4545	110	—	111	574	1.5	114	1.5	225
SPC 800-04	4	800.0	809.6	4	5050	125	—	111	737	4	127	12	245
SPC 1000-04	4	1000.0	1009.6	4	5050	125	—	111	937	1	127	12	245
SPC 1250-04	4	1250.0	1259.6	4	5050	125	—	111	1187	4	127	12	245


Taper Bore V-pulleys




TYPE1




TYPE2




TYPE3




TYPE4




TYPE5




TYPE6



TYPE7




TYPE8




TYPE9

PART NO.	NO. OF GROOVES	P.D	O.D	TYPE	BUSH NO.	MAX BORE	E	F	J	K	L	M	N
SPC 200-05	5	200.0	209.6	3	3535	90	—	136	150	23.5	89	23.5	—
SPC 212-05	5	212.0	221.6	3	3535	90	—	136	160	23.5	89	23.5	—
SPC 224-05	5	224.0	233.6	3	3535	90	—	136	173	23.5	89	23.5	—
SPC 236-05	5	236.0	245.6	3	3535	90	—	136	185	23.5	89	23.5	—
SPC 250-05	5	250.0	259.6	3	3535	90	—	136	198	23.5	89	23.5	—
SPC 265-05	5	265.0	274.6	3	3535	90	—	136	213	23.5	89	23.5	—
SPC 280-05	5	280.0	289.6	3	3535	90	—	136	228	23.5	89	23.5	—
SPC 300-05	5	300.0	309.6	6	3535	90	20	136	247	23.5	89	23.5	170
SPC 315-05	5	315.0	324.6	6	3535	90	20	136	264	23.5	89	23.5	170
SPC 335-05	5	335.0	344.6	6	3535	90	20	136	280	23.5	89	23.5	170
SPC 355-05	5	355.0	364.6	6	3535	90	20	136	304	23.5	89	23.5	170
SPC 375-05	5	375.0	384.6	6	3535	90	20	136	324	23.5	89	23.5	170
SPC 400-05	5	400.0	409.6	5	3535	90	—	136	344	23.5	89	23.5	170
SPC 425-05	5	425.0	434.6	5	4040	100	—	136	369	17	102	17	200
SPC 450-05	5	450.0	459.6	5	4040	100	—	136	394	17	102	17	200
SPC 475-05	5	475.0	484.6	5	4040	100	—	136	419	17	102	17	200
SPC 500-05	5	500.0	509.6	5	4040	100	—	136	444	17	102	17	200
SPC 530-05	5	530.0	539.6	5	4040	100	—	136	474	17	102	17	200
SPC 560-05	5	560.0	569.6	5	4545	110	—	136	504	11	114	11	225
SPC 630-05	5	630.0	639.6	5	5050	125	—	136	574	4.5	127	4.5	245
SPC 710-05	5	710.0	719.6	5	5050	125	—	136	654	4.5	127	4.5	245
SPC 800-05	5	800.0	809.6	5	5050	125	—	136	737	4.5	127	4.5	245
SPC 1000-05	5	1000.0	1009.6	5	5050	125	—	136	937	4.5	127	4.5	245
SPC 1250-05	5	1250.0	1259.6	5	5050	125	—	136	1187	4.5	127	4.5	245


Taper Bore V-pulleys




TYPE1




TYPE2




TYPE3




TYPE4




TYPE5




TYPE6



TYPE7




TYPE8




TYPE9

PART NO.	NO. OF GROOVES	P.D	O.D	TYPE	BUSH NO.	MAX BORE	E	F	J	K	L	M	N
SPC 200-06	6	200.0	209.6	3	3535	90	—	162	148	36.5	89	36.5	—
SPC 212-06	6	212.0	221.6	3	3535	90	—	162	160	36.5	89	36.5	—
SPC 224-06	6	224.0	233.6	3	3535	90	—	162	173	36.5	89	36.5	—
SPC 236-06	6	236.0	245.6	3	3535	90	—	162	185	36.5	89	36.5	—
SPC 250-06	6	250.0	259.6	3	3535	90	—	162	198	36.5	89	36.5	—
SPC 265-06	6	265.0	274.6	3	3535	90	—	162	213	36.5	89	36.5	—
SPC 280-06	6	280.0	289.6	3	3535	90	—	162	228	36.5	89	36.5	—
SPC 300-06	6	300.0	309.6	6	3535	90	20	162	247	36.5	89	36.5	170
SPC 315-06	6	315.0	324.6	6	3535	90	20	162	264	36.5	89	36.5	170
SPC 335-06	6	335.0	344.6	6	3535	90	20	162	280	36.5	89	36.5	170
SPC 355-06	6	355.0	364.6	6	3535	90	20	162	304	36.5	89	36.5	170
SPC 375-06	6	375.0	384.6	6	4040	100	20	162	324	30	102	30	200
SPC 400-06	6	400.0	409.6	6	4040	100	20	162	348	30	102	30	200
SPC 425-06	6	425.0	434.6	6	4545	110	30	162	369	24	114	24	225
SPC 450-06	6	450.0	459.6	6	4545	110	30	162	394	24	114	24	225
SPC 475-06	6	475.0	484.6	6	4545	110	30	162	419	24	114	24	225
SPC 500-06	6	500.0	509.6	5	4545	110	30	162	444	24	114	24	225
SPC 530-06	6	530.0	539.6	5	4545	110	30	162	474	24	114	24	225
SPC 560-06	6	560.0	569.6	5	5050	125	—	162	504	17.5	127	17.5	245
SPC 630-06	6	630.0	639.6	5	5050	125	—	162	574	17.5	127	17.5	245
SPC 710-06	6	710.0	719.6	5	5050	125	—	162	656	17.5	127	17.5	245
SPC 800-06	6	800.0	809.6	5	5050	125	—	162	737	17.5	127	17.5	245
SPC 1000-06	6	1000.0	1009.6	5	5050	125	—	162	937	17.5	127	17.5	245
SPC 1250-06	6	1250.0	1259.6	5	5050	125	—	162	1187	17.5	127	17.5	245


Taper Bore V-pulleys




TYPE1




TYPE2




TYPE3




TYPE4




TYPE5




TYPE6



TYPE7




TYPE8




TYPE9

PART NO.	NO. OF GROOVES	P.D	O.D	TYPE	BUSH NO.	MAX BORE	E	F	J	K	L	M	N
SPC 200-08	8	200.0	209.6	3	3535	90	—	213	148	62	89	62	—
SPC 212-08	8	212.0	221.6	3	3535	90	—	213	160	62	89	62	—
SPC 224-08	8	224.0	233.6	3	3535	90	—	213	170	62	89	62	—
SPC 236-08	8	236.0	245.6	3	3535	90	—	213	184	62	89	62	—
SPC 250-08	8	250.0	259.6	3	3535	90	—	213	198	62	89	62	—
SPC 265-08	8	265.0	274.6	3	3535	90	—	213	213	62	89	62	—
SPC 280-08	8	280.0	289.6	3	3535	90	—	213	228	62	89	62	—
SPC 300-08	8	300.0	309.6	3	4040	100	—	213	247	55.5	102	55.5	—
SPC 315-08	8	315.0	324.6	3	4040	100	—	213	258	55.5	102	55.5	—
SPC 335-08	8	335.0	344.6	6	4040	100	—	213	280	55.5	102	55.5	—
SPC 355-08	8	355.0	364.6	3	4040	100	—	213	304	55.5	102	55.5	—
SPC 375-08	8	375.0	384.6	3	4545	110	—	213	324	49.5	114	49.5	—
SPC 400-08	8	400.0	409.6	6	4545	110	20	213	348	49.5	114	49.5	220
SPC 425-08	8	425.0	434.6	6	5050	125	30	213	369	43	127	43	245
SPC 450-08	8	450.0	459.6	6	5050	125	30	213	394	43	127	43	245
SPC 475-08	8	475.0	484.6	6	5050	125	30	213	419	43	127	43	245
SPC 500-08	8	500.0	509.6	6	5050	125	30	213	444	43	127	43	245
SPC 530-08	8	530.0	539.6	6	5050	125	30	213	474	43	127	43	245
SPC 560-08	8	560.0	569.6	5	5050	125	—	213	504	43	127	43	245
SPC 630-08	8	630.0	639.6	5	5050	125	—	213	574	43	127	43	245
SPC 710-08	8	710.0	719.6	5	5050	125	—	213	656	43	127	43	245
SPC 800-08	8	800.0	809.6	5	5050	125	—	213	737	43	127	43	245
SPC 1000-08	8	1000.0	1009.6	5	5050	125	—	213	937	43	127	43	245
SPC 1250-08	8	1250.0	1259.6	5	5050	125	—	213	1187	43	127	43	245


Taper Bore V-pulleys




TYPE1




TYPE2




TYPE3




TYPE4




TYPE5




TYPE6



TYPE7



TYPE8



TYPE9

PART NO.	NO. OF GROOVES	P.D	O.D	TYPE	BUSH NO.	MAX BORE	E	F	J	K	L	M	N
SPC 250-10	10	250.0	259.6	3	4040	100	—	264	196	81	102	84	—
SPC 280-10	10	280.0	289.6	3	4040	100	—	264	226	81	102	81	—
SPC 300-10	10	300.0	309.6	3	4545	110	—	264	245	75	114	75	—
SPC 315-10	10	315.0	324.6	3	4545	110	—	264	258	75	114	75	—
SPC 355-10	10	355.0	364.6	3	4545	110	—	264	299	75	114	75	—
SPC 400-10	10	400.0	409.6	3	5050	125	—	264	342	68.5	127	68.5	—
SPC 450-10	10	450.0	459.6	6	5050	125	40	264	394	68.5	127	68.5	245
SPC 500-10	10	500.0	509.6	6	5050	125	40	264	444	68.5	127	68.5	245
SPC 560-10	10	560.0	569.6	5	5050	125	—	264	504	68.5	127	68.5	245
SPC 630-10	10	630.0	639.6	5	5050	125	—	264	574	68.5	127	68.5	245
SPC 710-10	10	710.0	719.6	5	5050	125	—	264	656	68.5	127	68.5	245
SPC 800-10	10	800.0	809.6	5	5050	125	—	264	737	68.5	127	68.5	245
SPC 1000-10	10	1000.0	1009.6	5	5050	125	—	264	937	68.5	127	68.5	245
SPC 1250-10	10	1250.0	1259.6	5	5050	125	—	264	1187	68.5	127	68.5	245

NOMENCLATURE FOR TAPER-FLUSH V-BELT PULLEY

SPB 250-06

