

Technical Data 230V



MODEL	Power (KW)	Current (A)	Speed (r/min)	Eff. (%)	Power factor	Tstart/Tn (Times)	Tmax/Tn (Times)	Starting Current (A)	Run Capacitor (μ f/V)	Noise dB(A)	W.t. (Kg)
MY561-2	0.09	0.79	2760	54	0.92	0.65	1.6	3	4 μ f/450V	67	2.9
MY562-2	0.12	0.98	2770	58	0.92	0.65	1.6	4	6 μ f/450V	67	3.2
MY563-2	0.18	1.42	2780	60	0.92	0.65	1.6	5	10 μ f/450V	69	3.5
MY631-2	0.18	1.33	2780	62	0.95	0.60	1.7	5	10 μ f/450V	70	4
MY632-2	0.25	1.76	2780	65	0.95	0.60	1.7	7	12 μ f/450V	70	4.5
MY711-2	0.37	2.53	2800	67	0.95	0.60	1.7	10	16 μ f/450V	75	5.1
MY712-2	0.55	3.49	2810	70	0.98	0.55	1.7	15	20 μ f/450V	75	7.2
MY801-2	0.75	4.62	2810	72	0.98	0.35	1.7	20	25 μ f/450V	75	9.6
MY802-2	1.1	6.51	2820	75	0.98	0.33	1.7	28	35 μ f/450V	78	11
MY90S-2	1.5	8.76	2820	76	0.98	0.30	1.8	40	45 μ f/450V	80	14
MY90L-2	2.2	12.7	2820	77	0.98	0.30	1.8	60	60 μ f/450V	80	16.5
MY100L-2	3.0	17.1	2840	78	0.98	0.28	1.8	75	80 μ f/450V	83	25
MY561-4	0.06	0.59	1360	48	0.92	0.75	1.6	2.5	4 μ f/450V	63	3.5
MY562-4	0.09	0.83	1370	51	0.92	0.75	1.6	3	6 μ f/450V	63	3.8
MY631-4	0.12	1.03	1380	55	0.92	0.65	1.6	3.5	10 μ f/450V	65	4
MY632-4	0.18	1.49	1390	57	0.92	0.65	1.5	5.5	12 μ f/450V	65	4.6
MY711-4	0.25	1.90	1400	61	0.94	0.50	1.5	8	14 μ f/450V	65	5.7
MY712-4	0.37	2.76	1400	62	0.94	0.50	1.5	10	16 μ f/450V	68	6.7
MY801-4	0.55	3.93	1400	64	0.95	0.35	1.7	15	20 μ f/450V	70	9.2
MY802-4	0.75	5.05	1410	68	0.95	0.33	1.7	20	25 μ f/450V	70	9
MY90S-4	1.1	6.87	1410	71	0.98	0.33	1.8	30	40 μ f/450V	73	14.5
MY90L-4	1.5	9.12	1420	73	0.98	0.30	1.8	40	45 μ f/450V	75	16.2
MY100L1-4	2.2	12.8	1440	76	0.98	0.28	1.8	60	70 μ f/450V	78	24
MY100L2-4	3	17.1	1440	78	0.98	0.28	1.8	75	90 μ f/450V	78	30
MYT711-2	0.37	2.61	2700	65	0.95	0.6	1.7	10.44	16 μ f/450V	75	5.1
MYT712-2	0.55	3.66	2700	68	0.96	0.70	1.7	15.6	20 μ f/450V	75	7.2
MYT801-2	0.75	4.73	2760	71	0.95	0.70	1.8	20	25 μ f/450V	75	9.8
MYT802-2	1.1	6.73	2720	72.5	0.98	0.65	1.7	26	35 μ f/450V	78	11.3
MYT90S-2	1.5	8.87	2800	75	0.98	0.6	1.8	38	45 μ f/450V	80	15
MYT90L-2	2.2	12.8	2800	76	0.98	0.6	1.7	58	60 μ f/450V	80	17.6
MYT100L-2	3	17.4	2800	76.5	0.98	0.5	1.8	81.5	80 μ f/450V	83	25.5
MYT711-4	0.25	1.97	1320	60	0.92	0.70	1.5	7.88	16 μ f/450V	65	5.7
MYT712-4	0.37	2.91	1320	60	0.92	0.70	1.5	11.66	20 μ f/450V	68	6.7
MYT801-4	0.55	4.17	1370	63	0.91	0.65	1.7	14	20 μ f/450V	73	9.7
MYT802-4	0.75	5.1	1370	67.3	0.95	0.63	1.65	18	30 μ f/450V	73	11.5
MYT90S-4	1.1	7.59	1350	68.5	0.92	0.55	1.7	27	40 μ f/450V	75	15.5
MYT90L-4	1.5	9.64	1370	72	0.94	0.55	1.7	35	45 μ f/450V	78	17.5
MYT100L1-4	2.2	14.05	1400	74	0.92	0.45	1.8	60	70 μ f/450V	80	26
MYT100L2-4	3	17.83	1400	77	0.95	0.45	1.7	76	90 μ f/450V	80	32

Note: MYT is high starting torque series single phase capacitor-run motors